

XtremeIPC VSN1190



VIDEO WALL CONTROLLER SOLUTION Advanced Graphics Display Technology



+ POWERFUL WALL CONTROLLER

The VSN1190 from EMS is a video wall controller capable of managing multiple video inputs and graphical outputs in order to drive large video wall installations. Suitable for a range of markets from security facilities to command and control rooms the VSN1190 provides a high performance, scalable solution in complex video environments.

Providing seamless compatibility with EMS's portfolio of Xtreme capture and Image graphics cards, the VSN1190 has been designed, developed and optimised to provide Ultra High Definition video & audio capture, including the capture of multiple, independent HDCP sources for display across the entire video wall.

+ INTEL® XEON PROCESSING

Incorporating an 11 slot PCIe backplane the VSN1190 is an industrial video wall processor. The PCIe switched fabric technology provides 11 x8 lane PCIe slots implemented with x16 physical connectors. Each slot is capable of providing up to 8GB/s bi-directional bandwidth allowing for high speed data transfer.

Each system includes the powerful EMS SBC3, a single board computer that features Dual Intel® Quad Core Xeon processors and up to 32GB of ECC compliant DDR3 memory and on-board graphics.

The flexibility of the Express11 Gen3 technology allows multiple backplanes to be arranged in a Star Configuration, providing the ability to create very large systems comprising several chassis, each with 11 available slots for video capture inputs and graphical outputs, connected via the optional HLink-G3/SLink-G3 expansion kit.



+ ADD FEATURES

When used in conjunction with EMS's Wall Control software, users of the VSN1190 are able to easily manage the entire video wall. Features of Wall Control software include the ability to: control video resolution and scale, cropping area, frame rate and position of the output on the video wall. The EMS Xtreme set of drivers allow OEM suppliers to build efficient display control and content management applications, making full use of the underlying hardware capability.

+ RELIABILITY

The VSN1190 video wall controller has been designed for use in demanding control room environments, which each component having been rigorously tested to ensure the highest levels of reliability and performance.

The VSN1190 can be pre-installed with Wall Monitor software, an application that monitors system temperature and includes alarm mechanisms that can warn operators if the system begins to operate outside of normal parameters.

+ MODELS AVAILABLE

Order Code: VSN1190-RPSU
Controller chassis with 800 Watt RPSU

Order Code: VSN1100X-RPSU
Expansion chassis with 800 Watt RPSU

All products are shipped with the latest software available, unless stated otherwise. Special requirements may be organised by contacting our Sales team.



+ SPECIFICATIONS

MOTHERBOARD

SBC4	Portwell ROBO8120 EC5549
Processor	Intel® Quad Core Xeon Clock speed 2.53 GHz Cache 8MB
Memory	16GB as standard (up to 32GB on request)
Ethernet	Dual 10Base-T/ 100Base-TX/ 1000 BaseT
On-board Graphics	DVI connection for control screen
RS232	For control

DISK STORAGE

HDD	2 x Western Digital RED 750GB Enterprise Grade RAID 1 configured
Optical Drive	DVD/ RW combo drive

CONNECTIVITY

USB	8 x 2.0 (2 front, 4 back, 2 internal*) *Internal ports for security dongles
-----	--

OPERATING SYSTEM

	Windows7 Ultimate 64 bit
--	--------------------------

BACKPLANE

Features	3rd generation PCIe switched fabric 11 slot x8 - 8GB/s uplink and downlink
----------	---

POWER

	800 Watt RPSU Dual Redundant
--	------------------------------

ENVIRONMENT

Operating Temperature	0 to 35 DegC (32 to 95 DegF)
Storage Temperature	-20 to 70 DegC (-4 to 158 DegF)
Relative Humidity	5% to 90% non-condensing
Noise	48.6dB (A) up to 67.9dB (A); Dependent on system config & ambient temp

DIMENSIONS

Length	500mm (including handles)
Height	175mm
Width	482.1mm
Weight	19 - 25kg
Shipped Weight	30 - 33kg

COMPLIANCE

	FCC/ CE/ ROHS/ UL (TBC)
--	-------------------------

We are continuously developing the technology used within our product ranges delivering outstanding innovative solutions, therefore the specification may change from time to time.